

<b>Produktsicherheit und -qualität</b> <i>Product Safety and Quality</i>	<b>Zertifikat Nr.</b> <i>Certificate No.</i>	<b>Unser Zeichen</b> <i>Our Reference</i>	<b>Anlage</b> <i>Appendix</i>
	S 50416644 0001	01- ZHM - 50170088 001	1

### Constructional Data Form (Page 3 of 3)

<b>1.1 License Holder:</b>	<b>ZHEJIANG EMMET FASTENER CO., LTD</b> <i>East side of Xichang Road, Hangzhou Bay Bridge New District, Haiyan Economic Development Zone 314304 P. R. China</i>
<b>1.2 Manufacturing Plant:</b>	<b>ZHEJIANG EMMET FASTENER CO., LTD</b> <i>East side of Xichang Road, Hangzhou Bay Bridge New District, Haiyan Economic Development Zone 314304 P. R. China</i>
<b>1.3 Product Identification:</b>	<b>Hydraulic Jack</b>
<b>1.4 Type Designation:</b>	<b>E1204; E1504; E1604; E2004</b>

#### 2.1 Dimensions: (mm)

No.	Description	E1204	E1504 E1604	E2004
1	Base	120x135	123x143	142x156
2	Handle	L500 (total); L265, Ø21,3, T1,4; L265, Ø17, T1,4	L600 (total); L316, Ø21,3, T1,4; L316, Ø17, T1,4	L700 (total); L365, Ø21,3 T1,4; L365, Ø17, T1,4
3	Stroke Piston	Ø43x Ø33	Ø48x Ø37	Ø53x Ø41
4	Cylinder	Ø89	Ø95	Ø114
5	Oil Tank	Ø55x Ø45	Ø60x Ø50	Ø68x Ø56
6	Saddle	M30	M33	M36
7	Head of Saddle	Ø40	Ø43	Ø46

#### 2.2 Weight: (kg)


	E1204	E1504 E1604	E2004
Jack (without handle)	6,1	7,0	9,4

#### 2.3 Material:

No.	Description	E1204	E1504 E1604	E2004
1	Base	QT350	QT350	QT350
2	Handle	Q235-A	Q235-A	Q235-A
3	Stroke Piston	45	45	45
4	Cylinder	Q235-A	Q235-A	Q235-A
5	Oil Tank	45	45	45
6	Saddle	45	45	45
7	Head of Saddle	45	45	45

#### 2.4 Other Technical Information:

	E1204	E1504 E1604	E2004
Permissible Load	12000 Kg	15000 Kg 16000 Kg	20000 Kg
Lifting Range	215-400 mm	225-425 mm	235-440 mm
Lifting Height	125 mm	140 mm	145 mm
Adjusting Height	60 mm	60 mm	60 mm
Safety Valve Setting	105-115% Permissible Load		

  
**TÜV Rheinland Group**

\_\_\_\_\_ (Place)

\_\_\_\_\_ (Date)

\_\_\_\_\_ (Stamp and signature of License holder)