

Produktsicherheit und -qualität
Product Safety and Quality

Zertifikat Nr.
Certificate No.

Unser Zeichen
Our Reference

Anlage
Appendix

S 50416644 0001

01- ZHM - 50170088 001

1

Constructional Data Form (Page 2 of 3)

1.1 License Holder: ZHEJIANG EMMET FASTENER CO., LTD
East side of Xichang Road, Hangzhou Bay Bridge New District, Haiyan Economic Development Zone 314304 P. R. China

1.2 Manufacturing Plant: ZHEJIANG EMMET FASTENER CO., LTD
East side of Xichang Road, Hangzhou Bay Bridge New District, Haiyan Economic Development Zone 314304 P. R. China

1.3 Product Identification: Hydraulic Jack

1.4 Type Designation: E0504; E0604; E0804; E1004

2.1 Dimensions: (mm)

No.	Description	E0504 E0604	E0804	E1004
1	Base	98x112	103x120	108x125
2	Handle	L400 (total); L215, Ø21,3, T1,4; L215, Ø17, T1,4	L400 (total); L215, Ø21,3, T1,4; L215, Ø17, T1,4	L500 (total); L265, Ø21,3 T1,4; L265, Ø17, T1,4
3	Stroke Piston	Ø32x Ø25	Ø38x Ø29	Ø40x Ø31
4	Cylinder	Ø70	Ø75	Ø80
5	Oil Tank	Ø43x Ø36	Ø48x Ø40	Ø52x Ø42
6	Saddle	M24	M26	M28
7	Head of Saddle	Ø30	Ø34	Ø36

2.2 Weight: (kg)


	E0504 E0604	E0804	E1004
Jack (without handle)	3,6	4,7	5,0

2.3 Material:

No.	Description	E0504 E0604	E0804	E1004
1	Base	QT350	QT350	QT350
2	Handle	Q235-A	Q235-A	Q235-A
3	Stroke Piston	45	45	45
4	Cylinder	Q235-A	Q235-A	Q235-A
5	Oil Tank	45	45	45
6	Saddle	45	45	45
7	Head of Saddle	45	45	45

2.4 Other Technical Information:

	E0504 E0604	E0804	E1004
Permissible Load	5000 Kg 6000 Kg	8000 Kg	10000 Kg
Lifting Range	185-355 mm	200-385 mm	200-385 mm
Lifting Height	110 mm	125 mm	125 mm
Adjusting Height	60 mm	60 mm	60 mm
Safety Valve Setting	105-115% Permissible Load		


25.09.2018
ZHM

TÜV Rheinland Group

(Place)

(Date)

(Stamp and signature of License holder)